

Leica DISTO™ D210

The original laser distance meter



Simply functional!

The compact and handy entry-level model has many interesting functions and is still simple to use. Addition and subtraction, area and volume calculations for rapid and reliable site measurement. The last 10 results are stored.

Leica DISTO $^{\text{TM}}$ D210 – leave the measuring tape behind.

Featured with:

Tel.: 03303 / 504066

Fax: 03303 / 504068

- Power Range Technology™
- IP54 dust and water splash protection
- Illuminated 3-line display
- Automatic multifunctional end-piece





Precision at the touch of a button

For everything you need to be accurate – the Leica DISTOTM D210 measures with an accuracy of \pm 1.0 mm.



Multifunctional end-piece

Whether measuring out of corners, slots or from edges, with this endpiece you are prepared for all measuring situations. The instrument detects the end-piece automatically, which helps you avoid expensive measuring errors.



Small and handy

Thanks to its ergonomic and compact design with soft grip, the Leica DISTO™ D210 sits securely in your hand, is lightweight and fits into any pocket.



Easy to read display

The results are shown on three lines. The display illumination means they can be clearly read, even in the dark.

Tel.: 03303 / 504066

Fax: 03303 / 504068



Leica DISTO™ D210

Art.No. 783648

- Leica DISTO[™] D210 laser distance meter
- Holster
- Hand loop Batteries

Technical Data

| ecililical Data | |
|--------------------------|-------------------------|
| General | |
| Typical measuring | ± 1 mm |
| accuracy | |
| Range | 80 m |
| Measuring units | 0.000 m, 0.0000 m, |
| | 0.00 m, 0.00 ft, 0'00" |
| | 1/32, 0.0 in, 0 in 1/32 |
| Power Range | • |
| Technology™ | |
| Distance in m | 10, 50, 100 m |
| Ø of the laser dot in mm | 6, 30, 60 mm |
| Protection class | IP54 – dust and |
| | splash water |
| | protected |
| Measurements | up to 5000 |
| per set of batteries | |
| Batteries | type AAA 2 x 1,5 V |
| Dimensions | 114 × 50 × 27 mm |
| Weight with batteries | 126 g |
| Functions | |
| Min/max measurement | • |
| Continuous | • |
| measurement | |
| Stake out function | • |
| Addition/subtraction | • |
| Area/volume | • |
| Painter function | • |
| Pythagoras | 2 and 3 points |
| Memory | 10 Results |
| Illuminated display | • |
| Multifunctional | with automatic |
| end-piece | recognition |

All illustrations, descriptions and technical specifications are subject to change without prior notice. Printed in Switzerland. Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012.





Laser Class 2 In accordance with IEC 60825-1

